(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 16 June 2005 (16.06.2005)

PCT

(10) International Publication Number WO 2005/054686 A1

(51) International Patent Classification7:

F15B 15/16

(21) International Application Number:

PCT/AU2004/001677

(22) International Filing Date:

26 November 2004 (26.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:


2003906725 2004904384 4 December 2003 (04.12.2003) AU 4 August 2004 (04.08.2004) ΑU

(71) Applicant (for all designated States except US): RA-ZORBACK VEHICLES CORPORATION LIMITED [AU/AU]; Unit 5, 9-11 Pitt Street, Mortdale, NSW 2223

- (72) Inventor; and
- (75) Inventor/Applicant (for US only): KENDALL, Jeffrey [AU/AU]; Unit 1/12 Streiff Road, Wingfield, SA 5013 (AU).
- (74) Agent: SPRUSON & FERGUSON; G.P.O. Box 3898, Sydney, NSW 2001 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: A PNEUMATIC OR HYDRAULIC CYLINDER LOCK ASSEMBLY



(57) Abstract: A hydraulic cylinder (10) having a piston rod (13) that receives a retaining member (38). Moving with the piston rod (13) are spherical lock members (26) that re moved radially by the retaining member (38) to lock the piston rod (13) in the retracted position. The retaining member (38) upon fluid under pressure being applied thereto is moved to a position permitting radially inward movement of the members (26) so that the rod (13) is released.

WO 2005/054686 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.